



Ordering Information

Catalog No.	Finish	Junction Box Mounting	Compatibility
6171WH 6171BK 6171AL	Matte White Matte Black Matte Aluminum	4" & 3 1/2" Octagonal, 4" & 3 1/2" Round	Alcyon HID: 23S20 Series, 23C20 Series, 23F20 Series. Also compatible with Alcyon Low and Line Voltage. Lytespan luminaires with single track mounting point. Not compatible for luminaires with adapter type 8171 and 6296.

Features

- Basic Lytespan Track Strip:** Die-cast with high-temperature impact-resistant thermoplastic insulator, supporting electrical contacts. Accepts Lytespan luminaires for individual applications.
- Junction Box Canopy:** Aluminum low-profile canopy, attached with two painted slotted cap screws (provided).
- Crossbar:** 0.074 steel, permanently fixed to track. Provides secure mounting of monopoint to electrical junction box.
- Supply Leads:** 16ga. White and Black, Green; insulated stranded wire.
- Locking Slot:** Accepts mechanical locking tab from Alcyon HID luminaire.

Electrical

Capacity is 120volts, 60Hz, 660W max. All Lytespan Track luminaires are polarized and continuously grounded throughout. Electrical conductors are concealed in an insulating liner. Intended for wiring to branch circuit building wire with ground. All wiring must be in accordance with National and Local Codes.

Use 90°C minimum supply wire to monopoint.

Finish

All Painted finishes are baked enamel.

Labels

UL listed, cULus

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • A0708